

# STORM e60-29 25th Anniversary

MATTE BLACK/SILVER/BLACK



1 819 EUR

1 959 EUR



FRAME SIZE	17.0" (M)	19.0" (L)	21.0" (XL)*
SEAT TUBE LENGTH (MM)	432	473	533
EFFECTIVE TOP TUBE LENGTH (MM)	602	623	640
STACK (MM)	625	635	635
REACH (MM)	411	429	446
CHAINSTAY LENGTH (MM)	460	460	460
WHEELBASE (MM)	1142	1164	1181
SEAT TUBE ANGLE	73	73	73
HEAD TUBE ANGLE	69	69	69
HEAD TUBE LENGTH (MM)	120	130	130
FORK LENGHT (MM)	510	510	510

FRAME SIZE	17.0" (M)	19.0" (L)	21.0" (XL)*
FORK OFFSET (MM)	46	46	46
BB DROP (MM)	45	45	45
HEAD TUBE SIZE	IHS 1-1/8"-1,5" (FSA NO.57B-1)		
SEAT POST DIAMETER (MM)	27.2	27.2	27.2
SEAT CLAMP DIAMETER (MM)	31.8	31.8	31.8
DROPOUT IDL (MM)	10x135 QR		
HANDLEBAR WIDTH (MM)	720 / 20 rise		
STEM LENGTH (MM)	70	70	70
CRANK LENGTH (MM)	170	170	170
SEATPOST LENGTH (MM)	350	350	350

FRAME	Alu 6061.T6 DAPU Multibutted
TRAVEL (F/R)	75 mm
FORK	SR Suntour MOBIE25-COIL RLR Remote LO
REAR SUSPENSION	-
SPRING/DAMPING SYSTEM	Coil spring/hydraulic lock-out
FREEWHEEL/CASSETTE	Shimano CS-HG200-9 11-36
HEAD SET	FSA No.10 Semi-Cartrige
SIZES	17" (M), 19" (L), 21" (XL)
MAX SUPPORT SPEED	25 km/h
DISTANCE RANGE (UP TO)	100 km (1st level of support)
COLOR	MATTE BLACK/BRICK RED/DARK GREY, MATTE BLACK/SILVER/BLACK
SIZES	19.0"(L), 17.0"(M), 21.0"(XL)
GEARS	1×9, 38x11-36
CRANKSET	DAPU Mid motor MD250S 38T w/ Alloy chain cover
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Altus RD-M2000-SGS Shadow
SHIFTER	Shimano Altus SL-M2000 RapidFire Plus
CHAIN	KMC X9e EPT
BB	DAPU
PEDALS	VP-831P
BRAKES	Shimano BR-MT200 hydraulic disc brake 160/160 mm
STEM	ONE Sport 31.8 mm
HANDLEBAR	Alloy rised
GRIPS	ONE Ergo Lock-on
SEAT POST	ONE Sport
SADDLE	WTB Volt 142
FRONT HUB	Shimano HB-M6010 CL 15x100 mm
REAR HUB	Shimano FH-M4050 CL QR
RIMS	WTB SX19 32H
SPOKES	Sapim Stainless Black
TIRES	WTB Nine Line Comp 29×2.25"
WEIGHT	23,5 kg / 19" (L) incl. battery
E-BIKE SYSTEM	BFI Sport Drive - Middle Drive Unit
BATTERY	Li-Ion 36 V / 504 Wh-14 A
DISPLAY	Compact display with control ring
DRIVE UNIT	Dapu MD250S, 36 V / 250 W / 90 Nm

**CHARGE CYCLES**

**CHARGING TIME (HOURS)**

1000 / 80 % of original capacity

2.5 hours / 4A – 7.5 hours / 2A (depending on charger and battery)