

AVALANCHE e50-26

GLOSS SILVER/SUOMI BLUE/BLACK

E-MOUNTAIN



E-BIKE

DRIVE UNIT	SHIMANO STEPS E7000, 36V, 250W, 60Nm
BATTERY	SHIMANO STEPS, BT-E8010, 36V, 504 Wh, frame mount
CHARGER	SHIMANO EC-E6002 2A, charging time up to 7.5 hours
CHARGE CYCLES	1000/60% of original capacity

FRAMESET

FRAME	Alloy Al-6061 T6 Custom tubing, Fat Fun Geometry, Shark Spine EVO 26er Fat, SHIMANO STEPS DU hanger, 4.8" Tire ready, Tapered Head Tube, Fat Boost 197x12, Disc Brake Post Mount, Replaceable RD Hanger, Inner Cable Routing
--------------	--

HEAD SET FSA Orbit 1.5E ZS No.57B -1

FORK eFat 26", Custom Alloy Tubing, 4.8" Tire ready, Fender&Carrier Ready, 1-1/8-1.5", Disc Brake Post Mount, 150x15 Thru axle

COLOUR GLOSS SILVER/SUOMI BLUE/BLACK

SIZES 17.0" (M), 19.0" (L)

DRIVETRAIN

GEARS	1x10
SHIFTER	SHIMANO DEORE SL-M6000-R RapidFire Plus, 10-speed
REAR DERAILLEUR	SHIMANO DEORE RD-M6000 Shadow Plus
CRANKSET	ONE1 ET39-F30-SHE80-L/R, 34T
CASSETTE	SHIMANO CS-HG500-10, 11-42T
CHAIN	KMC e10S
PEDALS	Marwi SP-160

COMPONENTS

HANDLEBAR	ONE1 Alloy, MTB AL-325BT, 6° upsweep, 9° backsweep, 25mm rise, 720mm, 31.8mm
STEM	ONE1 TDS-C342 Alloy, 31.8mm, +3°
GRIPS	Velo VLG-1777D2
BRAKES	SHIMANO BL-MT401/BR-MT400, 180/180 rotor, hydraulic disc brake, SHIMANO BL-MT401/BR-MT410, hydraulic disc brake
SADDLE	WTB Volt Sport
SEAT POST	ONE1 Alloy, SP C207, 30.9mm

* The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

WHEELS

TIRES Schwalbe Jumbo Jim Evolution, 26x4.80", ADDIX

GEOMETRY

FRAME SIZE	17.0" (M)	19.0" (L)
WHEEL SIZE	26"	26"
SEAT TUBE LENGTH (MM)	432	473
SEAT TUBE ANGLE (DEGREE)	74°	74°
EFFECTIVE TOP TUBE LENGTH (MM)	605	630
REACH (MM)	439	461
STACK HEIGHT (MM)	579	588
HEAD TUBE LENGTH (MM)	120	130
HEAD TUBE ANGLE (DEGREE)	68°	68°
CHAINSTAY LENGTH (MM)	500	500
BB DROP (MM)	35	35
WHEELBASE (MM)	1212	1239
HANDLEBAR WIDTH (MM)	720	720
STEM LENGTH (MM)	45	45
CRANK LENGTH (MM)	165	165
SEAT POST LENGTH (MM)	350	400